



## SERIE OS



 Ruota pesante in nylon 6 bianco. Buone capacità di carico, ridotto attrito ed ottima scorrevolezza. Resistente alla corrosione di olii, grassi animali ed alla maggior parte di prodotti chimici. Resiste alle temperature tra -30° e +80° C. La transizione vetrosa si aggira intorno i 50° C oltre si riducono le capacità di carico indicate in tabella. Adatta all'industria farmaceutica, chimica, alimentare e agli ambienti con elevata umidità. Ottima igienicità in quanto consente trattamenti di lavaggio e disinfezione.

MOZZO: K = Cuscinetti a sfera G = Foro passante R = Gabbia a rulli






SUPPORTO: Lamiera d'acciaio stampato e zincato, gruppo rotante realizzato con doppia corona di sfere.

 Heavy wheel in white nylon 6. Good load capacity, low friction and excellent smoothness. Resistant to the corrosion of animal fatty oils and most of chemical products. Withstands temperatures between -30 ° and + 80 ° C. The glass transition is around 50 ° C above the load capacities indicated in the table are reduced. Suitable for the pharmaceutical, chemical, food industry and environments with high humidity. Excellent hygiene as it allows washing and disinfection treatments.






HUB : K= Ball bearing G= Plain bore R = Roller bearing

BRACKET: Pressed steel, zinc plated. Swivel housing with double balls race ring.

## RUOTA

				M		ART.
80	30	40	15	G	150	R0N-G-080-15
80	30	30	15	K	150	R0N-K-080-15
100	45	58	20	G	500	R0S-G-100
100	45	50	20	K	500	R0S-K-100-20
100	45	50	25	K	500	R0S-K-100-25
100	40	49	15	R	350	R0S-R-100-AL
100	40	40	15	K	350	R0S-K-100-AL
125	45	58	20	G	600	R0S-G-125
125	45	50	20	K	600	R0S-K-125-20
125	45	50	25	K	600	R0S-K-125-25
125	45	49	20	R	400	R0S-R-125-AL
125	45	49	20	K	400	R0S-K-125-AL
150	45	58	20	G	600	R0S-G-150
150	45	50	20	K	600	R0S-K-150-20

## RUOTA

				M		ART.
150	45	50	25	K	600	R0S-K-150-25
150	50	59	20	R	600	R0S-R-150-AL
150	50	55	20	K	600	R0S-K-150-AL
160	50	55	20	K	600	R0S-K-160-20
160	50	55	25	K	600	R0S-K-160-25
160	50	59	20	R	700	R0S-R-160-AL
160	50	55	20	K	700	R0S-K-160-AL
175	45	54	20	G	800	R0S-G-175
175	45	50	20	K	800	R0S-K-175-20
175	45	50	25	K	800	R0S-K-175-25
200	50	58	20	G	1000	R0S-G-200
200	50	50	20	K	1000	R0S-K-200-20
200	50	50	25	K	1000	R0S-K-200-25
200	55	60	25	R	1000	R0S-R-200-AL
200	55	60	25	K	1000	R0S-K-200-AL
250	60	60	20	K	1200	R0S-K-250-20
250	60	60	25	K	1200	R0S-K-250-25

## MEDIO - PIASTRA FISSA



							M			ART.
80	30	108	100x85	80x60	9	G		150		453L-ONG080-15
80	30	108	100x85	80x60	9	K		150		453L-ONK080-15
100	40	135	100x85	80x60	9	R		350		453L-OSR100-AL
100	40	135	100x85	80x60	9	K		350		453L-OSK100-AL
100	45	152	134x114	105x80	12	G		500		453P-OSG100
100	45	152	134x114	105x80	12	K		500		453P-OSK100
125	45	161	100x88	80x60	9	R		400		453L-OSR125-AL
125	45	161	100x88	80x60	9	K		400		453L-OSK125-AL
125	45	164	134x114	105x80	12	G		600		453P-OSG125
125	45	164	134x114	105x80	12	K		600		453P-OSK125
150	50	194	134x114	105x80	12	R		600		453P-OSR150-AL
150	50	194	134x114	105x80	12	K		600		453P-OSK150-AL
150	45	194	134x114	105x80	12	G		600		453P-OSG150
150	45	194	134x114	105x80	12	K		600		453P-OSK150
160	50	199	134x114	105x80	12	R		600		453P-OSR160-AL
160	50	199	134x114	105x80	12	K		600		453P-OSK160-AL
160	50	199	134x114	105x80	12	K		600		453P-OSK160
175	45	230	134x114	105x80	12	G		600		453P-OSG175
175	45	230	134x114	105x80	12	K		600		453P-OSK175
200	55	243	134x114	105x80	12	R		600		453P-OSR200-AL
200	55	243	134x114	105x80	12	K		600		453P-OSK200-AL
200	50	243	134x114	105x80	12	G		600		453P-OSG200
200	50	243	134x114	105x80	12	K		600		453P-OSK200
250	60	308	134x114	105x80	12	K		1100		453I-OSK250

## MEDIO - PIASTRA GIREVOLE













							M			ART.	CON FRENO ART.
80	30	108	100x84	80x60	9	43	G	113	150	454L-ONG080-15	454LF-ONG080-15
80	30	108	100x84	80x60	9	43	K	113	150	454L-ONK080-15	454LF-ONK080-15
100	40	135	100x84	80x60	9	47	R	114	350	454L-OSR100-AL	454LF-OSR100-AL
100	40	135	100x84	80x60	9	47	K	114	350	454L-OSK100-AL	454LF-OSK100-AL
100	45	152	132x110	105x80	12	62	G	158	500	454P-OSG100	454PF-OSG100
100	45	152	132x110	105x80	12	62	K	158	500	454P-OSK100	454PF-OSK100
125	45	161	100x84	80x60	9	51	R	128	400	454L-OSR125-AL	454LF-OSR125-AL
125	45	161	100x84	80x60	9	51	K	128	400	454L-OSK125-AL	454LF-OSK125-AL
125	45	164	132x110	105x80	12	62	G	158	600	454P-OSG125	454PF-OSG125
125	45	164	132x110	105x80	12	62	K	158	600	454P-OSK125	454PF-OSK125
150	50	194	132x110	105x80	12	62	R	158	600	454P-OSR150-AL	454PF-OSR150-AL
150	50	194	132x110	105x80	12	62	K	158	600	454P-OSK150-AL	454PF-OSK150-AL
150	45	195	132x110	105x80	12	62	G	158	600	454P-OSG150	454PF-OSG150
150	45	195	132x110	105x80	12	62	K	158	600	454P-OSK150	454PF-OSK150
160	50	200	132x110	105x80	12	62	R	158	600	454P-OSR160-AL	454PF-OSR160-AL
160	50	200	132x110	105x80	12	62	K	158	600	454P-OSK160-AL	454PF-OSK160-AL
160	50	200	132x110	105x80	12	62	K	158	600	454P-OSK160	454PF-OSK160
175	45	230	132x110	105x80	12	61	G	158	600	454P-OSG175	454P-OSG175

175	45	230	132x110	105x80	12	61	K	158	600	454P-OSK175	454P-OSK175
200	55	242	132x110	105x80	12	61	R	158	600	454P-OSR200-AL	454PF-OSR200-AL
200	55	242	132x110	105x80	12	61	K	158	600	454P-OSK200-AL	454PF-OSK200-AL
200	50	242	132x110	105x80	12	61	G	158	600	454P-OSG200	454PF-OSG200
200	50	242	132x110	105x80	12	61	K	158	600	454P-OSK200	454PF-OSK200
250	60	308	132x110	105x80	12	63	K		1100	454I-OSK250	454IF-OSK250

## MEDIO - ATTACCO A FORO



										<b>ART.</b>	<b>CON FRENO ART.</b>
80	30	108	12	43	G	113	130			454LOB-ONG080-15	454LFOB-ONG080-15
80	30	108	12	43	K	113	130			454LOB-ONK080-15	454LFOB-ONK080-15
100	40	108	12	47	R	114	300			454LOB-OSR100-AL	454LFOB-OSR100-AL
100	40	108	12	47	K	114	300			454LOB-OSK100-AL	454LFOB-OSK100-AL
100	45	152	12	62	G	158	500			454POB-OSG100	454PFOB-OSG100
100	45	152	12	62	K	158	500			454POB-OSK100	454PFOB-OSK100
125	45	158	12	51	R	128	250			454LOB-OSR125-AL	454LFOB-OSR125-AL
125	45	158	12	51	K	128	250			454LOB-OSK125-AL	454LFOB-OSK125-AL
125	45	162	12	62	G	158	350			454POB-OSG125	454PFOB-OSG125
125	45	162	12	62	K	158	350			454POB-OSK125	454PFOB-OSK125
150	50	193	12	62	R	158	350			454POB-OSR150-AL	454PFOB-OSR150-AL
150	50	193	12	62	K	158	350			454POB-OSK150-AL	454PFOB-OSK150-AL
150	45	193	12	62	G	158	350			454POB-OSG150	454PFOB-OSG150
150	45	193	12	62	K	158	350			454POB-OSK150	454PFOB-OSK150
160	50	198	12	62	R	158	350			454POB-OSR160-AL	454PFOB-OSR160-AL
160	50	198	12	62	K	158	350			454POB-OSK160-AL	454PFOB-OSK160-AL
160	50	198	12	62	K	158	350			454POB-OSK160	454PFOB-OSK160
175	45	227	12	61	G	158	350			454POB-OSG175	454PFOB-OSG175
175	45	227	12	61	K	158	350			454POB-OSK175	454PFOB-OSK175
200	55	240	12	61	R	158	350			454POB-OSR200-AL	454PFOB-OSR200-AL
200	55	240	12	61	K	158	350			454POB-OSK200-AL	454PFOB-OSK200-AL
200	50	240	12	61	G	158	350			454POB-OSG200	454PFOB-OSG200
200	50	240	12	61	K	158	350			454POB-OSK200	454PFOB-OSK200