



SERIE 14



 Ruota con nucleo centrale in alluminio pressofuso e rivestimento in gomma elastica nera durezza 70 +/- 2 Shore A , mozzo con doppi cuscinetti a sfera . La particolare miscela e' resistente a temperature da -20° C a +70° C , possiede una buona resistenza all'abrasione e una notevole scorrevolezza che permette di impiegarla su pavimenti irregolari. Disponibile grigia in alcune misure.

MOZZO : K Cuscinetti a sfere






SUPPORTO : Lamiera d'acciaio stampata e zincata, gruppo rotante realizzato con doppia corona di sfere.

 Aluminium die-casting wheel with elastic black rubber 70 +/- 2 Shore A coating , hub on double ball bearings . The special compound lets it resist to temperatures from -20°C to + 70°C which good abrasion resistance and flowability, so that the wheel is also suitable for uneven flooring.

HUB : K = Ball bearing.

BRACKET: Pressed steel, zinc plated. Swivel housing with double balls race ring.

RUOTA

				M		ART.	ART. senza cuscinetti
100	40	40	12	K	150	R14-K-100	R14-100
125	40	45	12	K	150	R14-K-125-40	R14-125-40
125	50	60	20	K	220	R14-K-125-50-20	R14-125-50-20
125	50	60	25	K	220	R14-K-125-50-25	R14-125-50-25
160	50	60	20	K	330	R14-K-160-50-20	R14-160-50-20
160	50	60	25	K	330	R14-K-160-50-25	R14-160-50-25
180	50	60	20	K	350	R14-K-180-50-20	R14-180-50-20
180	50	60	25	K	350	R14-K-180-50-25	R14-180-50-25
200	50	60	20	K	400	R14-K-200-50-20	R14-200-50-20
200	50	60	25	K	400	R14-K-200-50-25	R14-200-50-25
250	50	60	20	K	525	R14-K-250-50-20	R14-250-50-20
250	50	60	25	K	525	R14-K-250-50-25	R14-250-50-25
300	60	60	30	K	650	R14-K-300	R14-300

MEDIO PESANTE - PIASTRA FISSA



						M		ART.
100	40	135	100x84	80x60	9	K	150	453L-14K-100
125	40	162	100x84	80x60	9	K	150	453L-14K-125-40
125	50	165	132x110	105x80	12	K	220	453P-14K-125-50
160	50	200	132x110	105x80	12	K	330	453P-14K-160
180	50	232	132x110	105x80	12	K	350	453P-14K-180
200	50	242	132x110	105x80	12	K	400	453P-14K-200
250	50	308	200x160	120x160	15	K	525	453I-14K-250
300	60	348	200x160	120x160	15	K	650	453I-14K-300

MEDIO - PESANTE - PIASTRA GIREVOLE



								M		ART.	CON FRENO ART.
100	40	135	100x84	80x60	9	47	K	114	150	454L-14K-100	454LF-14K-100
125	40	162	100x84	80x60	9	51	K	128	150	454L-14K-125-40	454LF-14K-125-40
125	50	165	132x110	105x80	12	61	K	158	220	454P-14K-125-50	454PF-14K-125-50
160	50	200	132x110	105x80	12	60	K	158	330	454P-14K-160	454PF-14K-160
180	50	232	132x110	105x80	12	59	K	158	350	454P-14K-180	454PF-14K-180
200	50	242	132x110	105x80	12	59	K	158	400	454P-14K-200	454PF-14K-200
250	50	308	200x160	120x160	15	63	K	150	525	454I-14K-250	454IF-14K-250
300	60	348	200x160	120x160	15	75	K	160	650	454I-14K-300	454IF-14K-300

MEDIO - PESANTE - ATTACCO A FORO



					M		ART.	CON FRENO ART.	
100	40	130	12	42	K	114	150	454POB-14K100	454PFOB-14K100
125	40	156	12	53	K	128	200	454POB-14K125-40	454PFOB-14K125-40
125	50	162	12	61	K	158	250	454POB-14K125-50	454PFOB-14K125-50
160	50	197	12	62	K	158	300	454POB-14K160	454PFOB-14K160
180	50	232	12	61	K	158	350	454POB-14K180	454PFOB-14K180
200	50	240	12	61	K	158	350	454POB-14K200	454PFOB-14K200