



SERIE 18 ELETTROSALDATO



 Ruota con nucleo centrale in ghisa meccanica con rivestimento in poliuretano colato 92 ± 2 Shore A. La particolare miscela consente di ottenere temperature d'impiego da - 30° C a + 80° C. La ruota è adatta a sopportare carichi elevati, garantendo una notevole scorrevolezza e una completa protezione dei pavimenti, anche nei momenti di massimo carico. La resistenza del poliuretano ai grassi ed ai vari oli (vegetali, animali, ecc.) è molto buona ed anche per altri prodotti chimici. Anche dopo diversi anni, la ruota conserva quasi inalterate le caratteristiche fisiche del poliuretano.

MOZZO: G = Foro liscio K = cuscinetti a sfera






SUPPORTO: Acciaio saldato e zincato, gruppo rotante realizzato con doppia corona di sfere.

 Wheel with iron die-casting centre and coating Polyurethane 92 + 2 Shore A casted. It is able to resist to temperatures from -30°C to +80°C. This wheel can support heavy loads and it has very good flowability and ensures flooring protection, also in the moment with maximum load. The polyurethane's resistance to greases and oils (both mineral and vegetables) is very high, also for chemical products. After many years, the wheel preserves the polyurethane physical properties.

HUB : G = smooth hole K = ball bearing






BRACKET: Heavy duty castor welded construction, zinc plated. Swivel housing with double balls race ring.

RUOTA CON CUSCINETTI

				M		ART.	ART. senza cuscinetti
80	40	40	20	K	350	R19-K-80-040	R19-80-040
100	40	47	15	K	350	R18-K-100-40-15	R18-100-40-S.35X11
100	40	45	20	K	350	R18-K-100-40-20	R18-100-40-S.42X12
100	60	60	20	K	700	R19-K-100-60	R19-100-60
125	50	50	25	K	600	R18-K-125-50	R18-125-50
150	50	50	25	K	700	R18-K-150-50	R18-150-50
180	50	50	25	K	900	R18-K-180-50	R18-180-50
200	40	45	25	K	750	R18-K-200-40	R18-200-40
200	50	52	25	K	1000	R18-K-200-50	R18-200-50
200	80	80	30	K	1500	R18-K-200-80	R18-200-80
250	50	60	25	K	1200	R18-K-250-50	R18-250-50
250	60	60	25	K	1500	R18-K-250-60	R18-250-60
250	80	80	30	K	1800	R18-K-250-80	R18-250-80

300	70	70	30	K	2100	R18-K-300-70	R18-300-70
300	80	80	30	K	2200	R18-K-300-80	R18-300-80
300	100	100	40	K	3000	R18-K-300-100	R18-300-100
350	100	100	40	K	3500	R18-K-350-100	R18-350-100
400	80	100	40	K	3300	R18-K-400-80	R18-400-80
400	100	100	40	K	3800	R18-K-400-100	R18-400-100

RUOTA CON FORO LISCIO

				M		ART.
100	30	36	15	G	250	R18-G-100-30-15
125	35	47	15	G	330	R18-G-125-35-15
150	40	47	20	G	500	R18-G-150-40-20
160	40	47	20	G	650	R18-G-160-40-20
175	40	52	20	G	700	R18-G-175-40-20
200	50	52	20	G	1000	R18-G-200-50-20
250	50	65	25	G	1200	R18-G-250-50-30
250	60	65	25	G	1500	R18-G-250-60-25
300	70	70	25	G	2100	R18-G-300-70-25
300	100	100	30	G	3000	R18-G-300-100-30
350	100	100	30	G	3500	R18-G-350-100-30
400	100	100	30	G	3800	R18-G-400-100-30

ELETTROSALDATO PESANTE - PIASTRA FISSA

						M		ART.
85	40	126	108x85	80x60	9	K	450	509L-19K85040
100	40	134	105x85	80x60	9	K	550	509L-19K100-40
100	60	134	135x110	105x80	12	K	700	509S-19K100-60
125	50	176	135x110	105x80	12	K	600	509S-18K125
150	50	190	135x110	105x80	12	K	700	509S-18K150
180	50	220	135x110	105x80	12	K	900	509S-18K180
200	50	250	135x110	105x80	12	K	1000	509S-18K200
250	60	300	135x110	105x80	12	K	1500	509S-18K250-60

ELETTROSALDATO PESANTE - PIASTRA GIREVOLE

							M		ART.	CON FRENO ART.
85	40	126	108x85	80x60	9	K	450	510L-19K85040	/	
100	40	134	105x85	80x60	9	K	550	510L-19K100-40	510LF-19K100-40	
100	60	134	135x110	105x80	12	K	700	510S-19K100-60	510SF-19K100-60	
125	50	176	135x110	105x80	12	K	600	510S-18K125	510SF-18K125	
150	50	190	135x110	105x80	12	K	700	510S-18K150	510SF-18K150	
180	50	220	135x110	105x80	12	K	900	510S-18K180	510SF-18K180	
200	50	250	135x110	105x80	12	K	1000	510S-18K200	510SF-18K200	
250	60	300	135x110	105x80	12	K	1500	510S-18K250-60	510S-18K250-60	

ELETTROSALDATO PESANTE DOPPIA RUOTA- PIASTRA FISSA

						M		ART.
125	50	176	175x140	140x105	13	K	1100	559G-18K125
150	50	190	175x140	140x105	13	K	1300	559G-18K150
180	50	217	175x140	140x105	13	K	1600	559G-18K180
200	50	250	175x140	140x105	13	K	1800	559G-18K200
250	50	300	250x200	210x160	17,5	K	2400	559M-18K250-50
250	60	330	250x200	210x160	17,5	K	3000	559M-18K250-60

ELETTROSALDATO PESANTE DOPPIA RUOTA - PIASTRA GIREVOLE

							M		ART.	CON FRENO ART.
125	50	176	175x140	140x105	13	75	K	1100	560G-18K125	560GF-18K125
150	50	190	175x140	140x105	13	75	K	1300	560G-18K150	560GF-18K150
180	50	217	175x140	140x105	13	75	K	1600	560G-18K180	560GF-18K180
200	50	250	175x140	140x105	13	75	K	1800	560G-18K200	560GF-18K200
250	50	300	250x200	210x160	17,5	91	K	2400	560M-18K250-50	560MF-18K250-50
250	60	330	250x200	210x160	17,5	91	K	3000	560M-18K250-60	560MF-18K250-60

ELETTROSALDATO EXTRA-PESANTE - PIASTRA FISSA

						M		ART.
200	80	250	200x160	160x120	17,5	K	1500	529J-18K200-80
200	100	255	200x160	160x120	17,5	K	1900	529J-18K200-100
250	80	300	200x160	160x120	17,5	K	1800	529J-18K250-80
250	100	317	200x160	160x120	17,5	K	2200	529J-18K250-100
300	80	380	200x160	160x120	17,5	K	2200	529J-18K300-80
300	100	383	200x160	160x120	17,5	K	2800	529J-18K300-100
350	100	425	250x200	210x160	17,5	K	3000	529M-18K350-100

ELETTROSALDATO EXTRA-PESANTE - PIASTRA GIREVOLE

						M		ART.	CON FRENO ART.
200	80	250	200x160	160x120	17,5	K	1500	530J-18K200-80	530JF-18K200-80
200	100	255	200x160	160x120	17,5	K	1900	530J-18K200-100	530JF-18K200-100
250	80	300	200x160	160x120	17,5	K	1800	530J-18K250-80	530JF-18K250-80
250	100	317	200x160	160x120	17,5	K	2200	530J-18K250-100	530JF-18K250-100
300	80	380	200x160	160x120	17,5	K	2200	530J-18K300-80	530JF-18K300-80
300	100	383	200x160	160x120	17,5	K	2800	530J-18K300-100	530JF-18K300-100
350	100	425	250x200	210x160	17,5	K	3000	530M-18K350-100	530JF-18K350-100

ELETTROSALDATO EXTRA-PESANTE DOPPIA RUOTA - PIASTRA FISSA

						M		ART.
200	80	250	200x160	160x120	17,5	K	2500	579J-18K200-80
250	80	300	200x160	160x120	17,5	K	3200	579J-18K250-80
300	70	381	250x200	210x160	17,5	K	3500	579M-18K300-70
300	100	383	250x200	210x160	17,5	K	4500	579M-18K300-100
350	100	425	250x200	210x160	17,5	K	5800	579M-18K350-100

ELETTROSALDATO EXTRA-PESANTE DOPPIA RUOTA - PIASTRA GIREVOLE

							M		ART.	CON FRENO ART.
200	80	250	200x160	160x120	17,5	75	K	2500	580J-18K200-80	580JF-18K200-80
250	80	300	200x160	160x120	17,5	85	K	3200	580J-18K250-80	580JF-18K250-80
300	70	381	250x200	210x160	17,5	106	K	3500	580J-18K300-80	580JF-18K300-80
300	100	383	250x200	210x160	17,5	106	K	4500	580J-18K300-100	580JF-18K300-100
350	100	425	250x200	210x160	17,5	101	K	5800	580M-18K350-100	580MF-18K350-100