


SERIE 19




 Rullo transpallet con nucleo centrale in tubo d'acciaio con rivestimento in poliuretano durezza 95 Shore A. E' resistente a temperature da - 30° C a + 80° C. Questo rullo è adatto a sopportare carichi elevati quando viene utilizzato su pavimentazioni compatte e prive di ondulazioni.

MOZZO: K = cuscinetti a sfera

SUPPORTO: Lamiera d'acciaio stampato oppure elettrosaldato, zincato.

ESECUZIONI STANDARD: 504L/505L = supporto stampato 504S/505S = supporto elettrosaldato





 Transpallet roller with steel tube centre and coating polyuretane 95 Shore A casted. It is able to resist to temperatures from -30°C to +80°C. This roller is suitable to support heavy loads when it is used on solid flooring.

HUB : K = ball bearing

BRACKET: Pressed or welded steel, zinc plated. Swivel housing with double balls race ring.


STANDARD EXECUTION: 504L/505L = pressed castor 504L/505L = welded castor

RULLO

			M		ART.	ART. senza cuscinetti
50	40	10	K	200	R19-K-50-040	R19-50-040
60	28	12	K	200	R19-K-60-28	R19-60-028
60	34		K	200	R19-K-60-034	R19-60-034
60	40	15	K	250	R19-K-60-040	R19-60-040
70	70	15	K	470	R19-K-70-070-15	R19-70-070-S.35
70	70	20	K	470	R19-K-70-070-20	R19-70-070-S.47
75	40	20	K	300	R19-K-75-040	R19-75-040
75	50	20	K	370	R19-K-75-050	R19-75-050
75	62	20	K	450	R19-K-75-062	R19-75-062
75	70	20	K	500	R19-K-75-070	R19-75-070
75	80	20	K	620	R19-K-75-080	R19-75-080
75	90	20	K	720	R19-K-75-090	R19-75-090
75	95	20	K	770	R19-K-75-095	R19-75-095

80	40	20	K	350	R19-K-80-040	R19-80-040
80	50	20	K	450	R19-K-80-050	R19-80-050
80	54	20	K	500	R19-K-80-054	R19-80-054
80	60	20	K	530	R19-K-80-060	R19-80-060
80	70	20	K	650	R19-K-80-070	R19-80-070
80	80	20	K	700	R19-K-80-080	R19-80-080
80	85	20	K	740	R19-K-80-085	R19-80-085
80	90	20	K	780	R19-K-80-090	R19-80-090
80	100	20	K	850	R19-K-80-100	R19-80-100
80	110	20	K	900	R19-K-80-110	R19-80-110
82	28	10	K	290	R19-K-82-028	R19-82-028
82	35	15	K	350	R19-K-82-035	R19-82-035
82	40	20	K	400	R19-K-82-040	R19-82-040
82	50	20	K	480	R19-K-82-050	R19-85-050
82	60	20	K	550	R19-K-82-060	R19-82-060
82	70	20	K	650	R19-K-82-070	R19-82-070
82	75	20	K	700	R19-K-82-075	R19-82-075
82	80	20	K	750	R19-K-82-080	R19-82-080
82	90	20	K	850	R19-K-82-090	R19-82-090
82	100	20	K	950	R19-K-82-100	R19-82-100
82	110	20	K	1030	R19-K-82-110	R19-82-110
82	120	20	K	1120	R19-K-82-120	R19-82-120
85	40	20	K	450	R19-K-85-040	R19-85-040
85	50	20	K	520	R19-K-85-050	R19-85-050
85	60	20	K	600	R19-K-85-060	R19-85-060
85	70	20	K	650	R19-K-85-070	R19-85-070
85	75	20	K	700	R19-K-85-075	R19-85-075
85	80	20	K	750	R19-K-85-080	R19-85-080
85	85	20	K	780	R19-K-85-085	R19-85-085
85	90	20	K	800	R19-K-85-090	R19-85-090
85	95	20	K	850	R19-K-85-095	R19-85-095
85	100	20	K	900	R19-K-85-100	R19-85-100
85	110	20	K	1000	R19-K-85-110	R19-85-110
85	120	20	K	1060	R19-K-85-120	R19-85-120
85	160	20	K	1200	R19-K-85-160	R19-85-160
100	40	20	K	560	R19-K-100-040	R19-100-040
100	50	20	K	620	R19-K-100-050	R19-100-050
100	60	20	K	700	R19-K-100-60	R19-100-060

PIASTRA FISSA



M



ART.

82	60	136	175x140	140x105	15	K	550	504L-19K82060	
82	70	137	175x140	140x105	15	K	650	504L-19K82070	
85	70	138,5	175x140	140x105	15	K	650	504L-19K85070	
82	60	131	135x110	105x80	12	K	550	504S-19K82060	
85	70	132,5	135x110	105x80	12	K	650	504S-19K85070	
85	80	132,5	135x110	105x80	12	K	750	504S-19K85080	

PIASTRA GIREVOLE



M



ART.

82	60	136	175x140	140x105	15	45	K	550	505L-19K82060
82	70	137	175x140	140x105	15	45	K	650	505L-19K82070
85	70	138,5	175x140	140x105	15	45	K	650	505L-19K85070
82	60	131	135x110	105x80	12	55	K	550	505S-19K82060
85	70	132,5	135x110	105x80	12	55	K	650	505S-19K85070
85	80	132,5	135x110	105x80	12	55	K	750	505S-19K85080