


SERIE 20




 Rullo transpallet in nylon 6 bianco di prima sceltare A. E' resistente a temperature da - 20° C a + 80° C. Questo rullo è adatto a lavorare in ambienti a contatto con acidi, oli e grassi. Questo rullo è adatto a sopportare carichi elevati quando viene utilizzato su pavimentazioni compatte e prive di ondulazioni.

MOZZO: K = cuscinetti a sfera

SUPPORTO: Lamiera d'acciaio stampato oppure elettrosaldato, zincato.

ESECUZIONI STANDARD: 504L/505L = supporto stampato 504S/505S = supporto elettrosaldato





 First quality white nylon 6 transpallet roller. It is able to resist to temperatures from -20°C to +80°C. This roller is suitable to work in areas where acids, oils and greases are used. It is suitable to use on solid flooring.

HUB : K = ball bearing


BRACKET: Pressed or welded steel, zinc plated. Swivel housing with double balls race ring.

STANDARD EXECUTION: 504L/505L = pressed castor 504L/505L = welded castor

RULLO

			M		ART.	ART. senza cuscinetti
50	40	10	K	250	R20-K-50-040-10	R20-50-040-S.32
50	40	15	K	250	R20-K-50-040-15	R20-50-040-S.35
82	40	20	K	550	R20-K-82-040	R20-82-040
82	60	20	K	600	R20-K-82-060	R20-82-060
82	70	20	K	650	R20-K-82-070	R20-82-070
82	80	20	K	680	R20-K-82-080	R20-80-080
82	90	20	K	775	R20-K-82-090	R20-82-090
82	100	20	K	900	R20-K-82-100	R20-82-100
85	50	20	K	500	R20-K-85-050	R20-85-050
85	60	20	K	550	R20-K-85-060	R20-85-060
85	70	20	K	650	R20-K-85-070	R20-85-70
85	75	20	K	700	R20-K-85-075	R20-85-075
85	80	20	K	750	R20-K-85-080	R20-85-080
85	90	20	K	850	R20-K-85-090	R20-85-090
85	100	20	K	950	R20-K-85-100	R20-85-100

PIASTRA FISSA



M



ART.

82	60	136	175x140	140x105	15	K	600	504L-20K82060	
82	70	137	175x140	140x105	15	K	650	504L-20K82070	
85	70	138,5	175x140	140x105	15	K	650	504L-20K85070	
82	60	131	135x110	105x80	12	K	600	504S-20K82060	
85	70	132,5	135x110	105x80	12	K	650	504S-20K85070	
85	80	132,5	135x110	105x80	12	K	750	504S-20K85080	

PIASTRA GIREVOLE



M



ART.

82	60	136	175x140	140x105	15	45	K	600	505L-20K82060
82	70	137	175x140	140x105	15	45	K	650	505L-20K82070
85	70	138,5	175x140	140x105	15	45	K	650	505L-20K85070
82	60	131	135x110	105x80	12	55	K	600	505S-20K82060
85	70	132,5	135x110	105x80	12	55	K	650	505S-20K85070
85	80	132,5	135x110	105x80	12	55	K	750	505S-20K85080