



SERIE 7 INOX



 Ruota con nucleo in polimero termoplastico nero e anello in gomma piena nera 80 Shore A a profilo trapezoidale. La miscela utilizzata in questo tipo di anello resiste senza subire alcuna alterazione delle proprie caratteristiche tecniche a temperature da -20°C a $+60^{\circ}\text{C}$ e può essere impiegata a contatto di acidi deboli, mentre perde le sue caratteristiche a contatto con olii e grassi.

MOZZO: G = Foro passante






SUPPORTO: Lamiera d'acciaio Inox AISI 304 Stampata, gruppo rotante realizzato con doppia corona di sfere.

 Wheel with black thermoplastic polymer centre, black solid rubber tyre hardness 80 Shore A with trapezoidal profile. The compound used for this tyre is able to resist at temperatures from -20°C to $+60^{\circ}\text{C}$. It can be used in contact with frail acids, but it loses its peculiarities in contact with oil and grease.

HUB : G = Plain bore

BRACKET: Pressed steel, Stainless Steel AISI 304. Swivel housing with double balls race ring.

RUOTA

				M		ART.
80	25	39	12	G	50	R7-G-080
100	30	39	12	G	70	R7-G-100
125	37,5	44	15	G	100	R7-G-125
150	40	44	15	G	130	R7-G-150
150	40	45	20	G	135	R7-G-150-20
160	40	45	20	G	150	R7-G-160
180	45	58	20	G	170	R7-G-180
200	50	58	20	G	205	R7-G-200
250	60	78	25	G	240	R7-G-250

LEGGERO - PIASTRA FISSA



						M		ART.
80	25	108	101x84	80x60	9	G	50	443X-7G080
100	30	127	101x84	80x60	9	G	70	443X-7G100
125	37,5	156	100x84	80x60	9	G	100	443X-7G125
125	37,5	164	135x110	105x80	11	G	100	443PX-7G125
150	40	181	100x85	80x60	9	G	120	443LX-7G150
150	40	192	135x110	105x80	11	G	135	443PX-7G150
160	40	197	135x110	105x80	11	G	150	443X-7G160
180	50	230	135x110	105x80	11	G	170	443X-7G180
200	50	240	135x110	105x80	11	G	205	443X-7G200

LEGGERO - PIASTRA GIREVOLE



							M			ART.	CON FRENO ART.
80	25	108	95x80	80x60	9	32	G	110	50	444X-7G080	444XF-7G080
100	30	127	95x80	80x60	9	32	G	110	70	444X-7G100	444XF-7G100
125	37,5	156	95x80	80x60	9	32	G	113	100	444X-7G125	444XF-7G125
125	37,5	164	129x106	105x80	11	52	G	150	100	444PX-7G125	444PXF-7G125
150	40	181	100x85	80x60	9	45	G	115	120	444LX-7G150	444LXF-7G150
150	40	192	129x106	105x80	11	52	G	150	135	444X-7G150	444XF-7G150
160	40	197	129x106	105x80	11	52	G	150	150	444X-7G160	444XF-7G160
180	50	230	129x106	105x80	11	48	G	150	170	444X-7G180	444XF-7G180
200	50	240	129x106	105x80	11	48	G	150	205	444X-7G200	444XF-7G200

LEGGERO - ATTACCO A FORO



					M				ART.	CON FRENO ART.
80	25	108	12	32	G	110	50	444XOB-7G080	444XFOB-7G080	
100	30	127	12	32	G	110	70	444XOB-7G100	444XFOB-7G100	
125	37,5	156	12	32	G	113	100	444XOB-7G125	444XFOB-7G125	
125	37,5	164	16	52	G	113	100	444PXOB-7G125	444PXFOB-7G125	
150	40	181	12	120	G	115	120	444LXOB-7G150	444LXFOB-7G150	
150	40	192	16	52	G	115	135	444XOB-7G150	444XFOB-7G160	
160	40	197	16	52	G	115	150	444XOB-7G160	444XFOB-7G160	
180	50	230	16	48	G	150	170	444XOB-7G180	444XFOB-7G180	
200	50	240	16	48	G	150	205	444XOB-7G200	444XFOB-7G200	