



SERIE 9 / 232



 Ruota con nucleo centrale in nylon 6 bianco, rivestito in poliuretano termoplastico 98 shore A ad iniezione . Buona capacità di carico, ridotta rumorosità, non danneggia il pavimento, resiste ad olii, grassi. Resistente alla rottura , corrosione ed alla maggior parte dei prodotti chimici. Ottimo impiego nell'industria chimico-farmaceutica ,arredamento e alimentare. Disponibili nei colori rosso e grigio. Resistente a temperature: -20° C + 60° C

MOZZO: G = Foro passante K = Cuscinetti a sfera






SUPPORTO: Lamiera d'acciaio stampato e zincato, gruppo rotante realizzato con doppia corona di sfere.

 Thermoplastic injected polyurethane tyred wheel with nylon 6 centre .It has hardness 98 shore A . This wheel has very good load capacity ,low noist ,flooring protection and resists to corroding substances,mineral oils and greases.This type of wheel can be used to pharmaceutical, chemical,food and automotive industries. It resists at temperatures from - 20° C to + 60° C

HUB : G= Plain bore K= Ball bearing

BRACKET: Pressed steel, zinc plated. Swivel housing with double balls race ring.

RUOTA

				M		ART.
35	27	27	6	K	100	R19-K-035
40	18	22	6	G	50	R9-G040
50	18	22	6	G	50	R9-G050
60	25	29	8	G	80	R9-G060
75	25	29	12	G	100	R9-G075
80	25	29	12	G	100	R9-G080

LEGGERO - PIASTRA FISSA



						M		ART.
40	18	61	42x42	30x30	6	G	50	231L-9G040
50	18	66	42x42	30x30	6	G	50	231L-9G050
60	25	82	60x60	46x46	6	G	80	231-9G060
60	25	85	63x50	49x36	6	G	80	231P-9G060
75	25	101	60x60	46x46	6	G	60	231-9G075
80	25	104	60x60	46x46	6	G	60	231-9G080

LEGGERO - PIASTRA GIREVOLE



						M		ART.	CON FRENO ART.	
35	27	53	60x60	46x46	6	15	K	100	232-19K035	232F-19K035
40	18	61	42x42	30x30	6	24	G	50	232L-9G040	232LF-9G040
50	18	66	42x42	30x30	6	24	G	50	232L-9G050	232LF-9G050
60	25	82	60x60	46x46	6	21	G	80	232-9G060	232F-9G060
60	25	85	63x50	49x36	6	24	G	80	232P-9G060	232PF-9G060
75	25	101	60x60	46x46	6	30	G	60	232-9G075	232F-9G075
80	25	104	60x60	46x46	6	30	G	60	232-9G080	232F-9G080

LEGGERO - ATTACCO A FORO



					M		ART.	CON FRENO ART.
35	27	53	10-12	15	K	100	232OB-19K035	232OFB-19K035
40	18	61	08-10	24	G	50	232LOB-9G040	232LFB-9G040
50	18	66	08-10	24	G	50	232LOB-9G050	232LFB-9G050
60	25	82	10-12	21	G	80	232OB-9G060	232OFB-9G060
75	25	101	10-12	30	G	60	232OB-9G075	232OFB-9G075
80	25	104	10-12	30	G	60	232OB-9G080	232OFB-9G080

LEGGERO - ATTACCO FILETTATO



					M		ART.	CON FRENO ART.
35	27	53	M10x25	15	K	100	232M10-19K035	232FM10-19K035
35	27	53	M12x25	15	K	100	232M12-19K035	232FM12-19K035
40	18	61	M8x15	24	G	50	232LM8-9G040	232LFM8-9G040
40	18	61	M10x20	24	G	50	232LM10-9G040	232LFM10-9G040
50	18	66	M8x15	24	G	50	232LM8-9G050	232LFM8-9G050
50	18	66	M10x20	24	G	50	232LM10-9G050	232LFM10-9G050
60	25	82	M10x25	21	G	80	232M10-9G060	232FM10-9G060
60	25	82	M12x25	21	G	80	232M12-9G060	232FM12-9G060
75	25	101	M10x25	30	G	60	232M10-9G075	232FM10-9G075
75	25	101	M12x25	30	G	60	232M12-9G075	232FM12-9G075
80	25	104	M10x25	30	G	60	232M10-9G080	232FM10-9G080
80	25	104	M12x25	30	G	60	232M12-9G080	232FM12-9G080