



SERIE ON INOX



 Ruota In nylon 6 bianco. Buone capacita' di carico, ridotto attrito ed ottima scorrevolezza . Resistente alla corrosione di olii, grassi animali ed alla maggior parte di prodotti chimici .Resiste alle temperature tra -30° e +80° C. La transizione vetrosa si aggira intorno i 50° C oltre si riducono le capacita' di carico indicate in tabella. Adatta all'industria farmaceutica, chimica, alimentare e agli ambienti con elevata umidita'. Ottima igienicita' in quanto consente trattamenti di lavaggio e disinfezione.

MOZZO: RX = Cuscinetto a rulli Inox KS = Cuscinetti a sfere stagno G= Foro Passante






SUPPORTO: Lamiera d'acciaio Inox AISI 304 stampata, gruppo rotante realizzato con doppia corona di sfere.






 Wheel In white nylon 6 . Good load capacity, low friction and excellent smoothness. Resistant to the corrosion of animal fatty oils and most of chemical products. Withstands temperatures between -30 ° and + 80 ° C. The glass transition is around 50 ° C above the load capacities indicated in the table are reduced. Suitable for the pharmaceutical, chemical, food industry and environments with high humidity. Excellent hygiene as it allows washing and disinfection treatments.

HUB : RX = Stainless steel Roller bearing. K= Ball bearing G= Plain bore

BRACKET: Pressed steel, Stainless steel AISI 304. Swivel housing with double balls race ring.

RUOTA

				M		ART.
60	30	40	12	G	120	RON-G-060
80	30	40	12	G	130	RON-G-080
80	30	40	12	RX	150	RON-RX-080
80	30	30	15	KS	150	RON-KS-080-15
100	35	40	12	G	150	RON-G-100
100	35	40	15	G	180	RON-G-100-15
100	30	30	15	RX	160	RON-RX-100
100	35	45	15	KS	160	RON-KS-100
125	40	48	15	G	250	RON-G-125
125	40	45	15	RX	300	RON-RX-125
125	40	45	15	KS	300	RON-KS-125
125	45	58	20	G	500	R0S-G-125
125	45	50	20	KS	500	R0S-KS-125

				M		ART.
150	40	49	15	G	270	R0N-G-150
150	40	45	15	RX	400	R0N-RX-150
150	40	58	20	G	380	R0N-G-150-20
150	40	58	20	RX	400	R0N-RX-150-20
150	40	50	20	KS	400	R0N-KS-150-20
175	50	59	20	G	290	R0N-G-175
175	45	58	20	RX	450	R0N-RX-175
175	50	55	20	KS	450	R0N-KS-175
200	50	59	20	G	320	R0N-G-200
200	50	58	20	RX	500	R0N-RX-200
200	50	55	20	KS	500	R0N-KS-200

LEGGERO - PIASTRA FISSA



						M		ART.
60	30	89	100x85	80x60	9	G	120	443X-ONG060
80	30	108	100x84	80x60	9	G	130	443X-ONG080
80	30	108	100x84	80x60	9	RX	150	443X-ONRX080
80	30	108	100x84	80x60	9	KS	150	443X-ONKS080
100	35	127	100x84	80x60	9	G	150	443X-ONG100
100	35	127	100x84	80x60	9	G	180	443X-ONG100-15
100	35	127	100x84	80x60	9	RX	160	443X-ONRX100
100	35	127	100x84	80x60	9	KS	160	443X-ONKS100
125	40	156	100x84	80x60	9	G	200	443X-ONG125
125	40	156	100x84	80x60	9	RX	200	443X-ONRX125
125	40	156	100x84	80x60	9	KS	200	443X-ONKS125
125	45	164	135x110	105x80	11	G	300	443PX-OSG125
125	45	164	135x110	105x80	11	KS	300	443PX-OSKS125
150	40	181	100x85	80x60	9	G	200	443LX-ONG150
150	40	181	100x85	80x60	9	RX	200	443LX-ONRX150
150	40	181	100x85	80x60	9	KS	200	443LX-ONKS150
150	40	192	135x110	105x80	11	G	300	443X-ONG150
150	40	192	135x110	105x80	11	RX	300	443X-ONRX150
150	40	192	135x110	105x80	11	KS	300	443X-ONKS150
175	50	228	135x110	105x80	11	G	290	443X-ONG175
175	45	228	135x110	105x80	11	RX	300	443X-ONRX175
175	50	228	135x110	105x80	11	KS	300	443X-ONKS175
200	50	240	135x110	105x80	11	G	300	443X-ONG200
200	50	240	135x110	105x80	11	RX	300	443X-ONRX200
200	50	240	135x110	105x80	11	KS	300	443X-ONKS200

LEGGERO - PIASTRA GIREVOLE



								M		ART.	CON FRENO ART.
60	30	89	100x85	80x60	9	37	G	110	120	444X-ONG060	444XF-ONG060
80	30	108	95x80	80x60	9	32	G	110	130	444X-ONG080	444XF-ONG080
80	30	108	95x80	80x60	9	32	RX	110	130	444X-ONRX080	444XF-ONRX080
80	30	108	95x80	80x60	9	32	KS	110	130	444X-ONKS080	444XF-ONKS080
100	35	127	95x80	80x60	9	32	G	110	130	444X-ONG100	444XF-ONG100
100	35	127	95x80	80x60	9	32	G	110	130	444X-ONG100-15	444XF-ONG100-15
100	30	127	95x80	80x60	9	32	RX	110	130	444X-ONRX100	444XF-ONRX100
100	35	127	95x80	80x60	9	32	KS	110	130	444X-ONKS100	444XF-ONKS100
125	40	156	95x80	80x60	9	32	G	113	130	444X-ONG125	444XF-ONG125
125	40	156	95x80	80x60	9	32	RX	113	130	444X-ONRX125	444XF-ONRX125
125	40	156	95x80	80x60	9	32	KS	113	130	444X-ONKS125	444XF-ONKS125
125	45	164	129x106	105x80	11	52	G	150	300	444PX-OSG125	444PXF-OSG125
125	45	164	129x106	105x80	11	52	KS	150	300	444PX-OSKS125	444PXF-OSKS125

										ART.	CON FRENO ART.
150	40	181	100x85	80x60	9	45	G	113	200	444LX-ONG150	444LXF-ONG-150
150	40	181	100x85	80x60	9	45	RX	113	200	444LX-ONRX150	444LXF-ONRX150
150	40	192	129x106	105x80	11	52	G	150	300	444X-ONG150-20	444XF-ONG150-20
150	40	192	129x106	105x80	11	52	RX	150	300	444X-ONRX150-20	444XF-ONRX150-20
150	40	192	129x106	105x80	11	52	KS	150	300	444X-ONKS150-20	444XF-ONKS150-20
175	50	228	129x106	105x80	11	48	G	150	300	444X-ONG175	444XF-ONG175
175	45	228	129x106	105x80	11	48	RX	150	300	444X-ONRX175	444XF-ONRX175
175	50	228	129x106	105x80	11	48	KS	150	300	444X-ONKS175	444XF-ONKS175
200	50	240	129x106	105x80	11	48	G	150	300	444X-ONG200	444XF-ONG200
200	50	240	129x106	105x80	11	48	RX	150	300	444X-ONRX200	444XF-ONRX200
200	50	240	129x106	105x80	11	48	KS	150	300	444X-ONKS200	444XF-ONKS200

LEGGERO - ATTACCO A FORO



										ART.	CON FRENO ART.
60	30	87	12	37	G	110			120	444XOB-ONG060	444XFOB-ONG060
60	30	87	12	37	RX	110			120	444XOB-ONR060	444XFOB-ONRX060
60	30	87	12	37	KS	110			120	444XOB-ONKS060	444XFOB-ONKS060
80	30	108	12	32	G	110			130	444XOB-ONG080	444XFOB-ONG080
80	30	108	12	32	RX	110			130	444XOB-ONR080	444XFOB-ONR080
80	30	108	12	32	KS	110			130	444XOB-ONK080	444XFOB-ONK080
100	35	127	12	32	G	110			130	444XOB-ONG100	444XFOB-ONG100
100	35	127	12	32	G	110			130	444XOB-ONG100-15	444XFOB-ONG100-15
100	30	127	12	32	RX	110			130	444XOB-ONRX100	444XFOB-ONRX100
100	35	127	12	32	KS	110			130	444XOB-ONKS100	444XFOB-ONKS100
125	40	156	12	32	G	113			130	444XOB-ONG125	444XFOB-ONG125
125	40	156	12	32	RX	113			130	444XOB-ONRX125	444XFOB-ONRX125
125	40	156	12	32	KX	113			130	444XOB-ONKS125	444XFOB-ONKS125
125	45	164	16	52	G	113			300	444XPOB-ONG125-20	444XPFOB-ONG125-20
125	45	164	16	52	KS	113			300	444XPOB-ONKS125-20	444XPFOB-ONKS125-20
150	40	178	12	45	G	115			200	444LXOB-ONG150	444LXF-ONG150
150	40	178	12	45	RX	115			200	444LXOB-ONRX150	444LXF-ONRX150
150	40	192	16	52	G	115			300	444XOB-ONG150-20	444XFOB-ONG150-20
150	40	192	16	52	RX	115			300	444XOB-ONRX150-20	444XFOB-ONRX150-20
150	40	192	16	52	KS	115			300	444XOB-ONKS150-20	444XFOB-ONKS150-20
175	50	228	16	48	G	150			300	444XOB-ONG175	444XFOB-ONG175
175	45	228	16	48	RX	150			300	444XOB-ONRX175	444XFOB-ONRX175
175	50	228	16	48	KS	150			300	444XOB-ONKS175	444XFOB-ONKS175
200	50	240	16	48	G	150			300	444XOB-ONG200	444XFOB-ONG200
200	50	240	16	48	RX	150			300	444XOB-ONRX200	444XFOB-ONRX200
200	50	240	16	48	KS	150			300	444XOB-ONKS200	444XFOB-ONKS200

POSSIBILITA' DI MONTARE PERNI LISCI E FILETTATI SU RICHIESTA