



SERIE OS ELETTROSALDATO



 Ruota pesante in nylon 6 bianco. Ottima capacita' di carico, attrito ridotto ed ottima scorrevolezza. Adatta all'industria farmaceutica, chimica, alimentare e agli ambienti con elevata umidita'. Resistente alla corrosione di olii, grassi animali ed alla maggior parte di prodotti chimici. Resiste alle temperature tra -30° e +80° C. Ottima igienicita' in quanto consente trattamenti di lavaggio e disinfezione.

MOZZO: G = Foro passante K = Cuscinetti a sfera






SUPPORTO: Acciaio saldato e zincato, gruppo rotante realizzato con doppia corona di sfere.

 Heavy range white nylon 6 wheel. High flowability with full load on smooth flooring. Suitable for the pharmaceutical, chemical, food industry and environments with high humidity. Resistant to the corrosion of fatty animal oils and most of chemical products. It is able to resist at temperatures from -30 ° to + 80 ° C. Good hygienics as it allows washing and disinfection treatments.

HUB : G = Plain bore K = Ball bearing

BRACKET: Heavy duty castor welded construction, zinc plated. Swivel housing with double balls race ring.

RUOTA

|  |  |  |  | M |  | ART. |
|---|---|---|---|---|---|--------------|
| 100 | 45 | 58 | 20 | G | 500 | R0S-G-100 |
| 100 | 45 | 50 | 20 | K | 500 | R0S-K-100-20 |
| 100 | 45 | 50 | 25 | K | 500 | R0S-K-100-25 |
| 125 | 45 | 58 | 20 | G | 600 | R0S-G-125 |
| 125 | 45 | 50 | 20 | K | 600 | R0S-K-125-20 |
| 125 | 45 | 50 | 25 | K | 600 | R0S-K-125-25 |
| 150 | 45 | 58 | 20 | G | 600 | R0S-G-150 |
| 150 | 45 | 50 | 20 | K | 600 | R0S-K-150-20 |
| 150 | 45 | 50 | 25 | K | 600 | R0S-K-150-25 |
| 175 | 45 | 54 | 20 | G | 800 | R0S-G-175 |
| 175 | 45 | 50 | 20 | K | 800 | R0S-K-175-20 |
| 175 | 45 | 50 | 25 | K | 800 | R0S-K-175-25 |
| 200 | 50 | 58 | 20 | G | 1000 | R0S-G-200 |

| | | | | | | |
|-----|----|----|----|---|------|--------------|
| 200 | 50 | 50 | 20 | K | 1000 | ROS-K-200-20 |
| 200 | 50 | 50 | 25 | K | 1000 | ROS-K-200-25 |
| 250 | 60 | 60 | 20 | K | 1200 | ROS-K-250-20 |
| 250 | 60 | 60 | 25 | K | 1200 | ROS-K-250-25 |

ELETTROSALDATO PESANTE - PIASTRA FISSA

| | | | | | | M | | ART. |
|-----|----|-----|---------|--------|----|---|------|-------------|
| 100 | 45 | 134 | 105x85 | 80x60 | 9 | G | 500 | 509L-OSG100 |
| 100 | 45 | 134 | 105x85 | 80x60 | 9 | K | 500 | 509L-OSK100 |
| 125 | 45 | 176 | 135x110 | 105x80 | 12 | G | 600 | 509S-OSG125 |
| 125 | 45 | 176 | 135x110 | 105x80 | 12 | K | 600 | 509S-OSK125 |
| 150 | 45 | 190 | 135x110 | 105x80 | 12 | G | 600 | 509S-OSG150 |
| 150 | 45 | 190 | 135x110 | 105x80 | 12 | K | 600 | 509S-OSK150 |
| 175 | 45 | 217 | 135x110 | 105x80 | 12 | G | 800 | 509S-OSG175 |
| 175 | 45 | 217 | 135x110 | 105x80 | 12 | K | 800 | 509S-OSK175 |
| 200 | 50 | 250 | 135x110 | 105x80 | 12 | G | 1000 | 509S-OSG200 |
| 200 | 50 | 250 | 135x110 | 105x80 | 12 | K | 1000 | 509S-OSK200 |
| 250 | 60 | 300 | 135x110 | 105x80 | 12 | K | 1200 | 509S-OSK250 |

ELETTROSALDATO PESANTE - PIASTRA GIREVOLE

| | | | | | | | M | | ART. | CON FRENO ART. |
|-----|----|-----|---------|--------|----|---|------|-------------|--------------|----------------|
| 100 | 45 | 134 | 105x85 | 80x60 | 9 | G | 500 | 510L-OSG100 | 510LF-OSG100 | |
| 100 | 45 | 134 | 105x85 | 80x60 | 9 | K | 500 | 510L-OSK100 | 510LF-OSK100 | |
| 125 | 45 | 176 | 135x110 | 105x80 | 12 | G | 600 | 510S-OSG125 | 510SF-OSG125 | |
| 125 | 45 | 176 | 135x110 | 105x80 | 12 | K | 600 | 510S-OSK125 | 510SF-OSK125 | |
| 150 | 45 | 190 | 135x110 | 105x80 | 12 | G | 600 | 510S-OSG150 | 510SF-OSG150 | |
| 150 | 45 | 190 | 135x110 | 105x80 | 12 | K | 600 | 510S-OSK150 | 510SF-OSK150 | |
| 175 | 45 | 217 | 135x110 | 105x80 | 12 | G | 800 | 510S-OSG175 | 510SF-OSG175 | |
| 175 | 45 | 217 | 135x110 | 105x80 | 12 | K | 800 | 510S-OSK175 | 510SF-OSK175 | |
| 200 | 50 | 250 | 135x110 | 105x80 | 12 | G | 1000 | 510S-OSG200 | 510SF-OSG200 | |
| 200 | 50 | 250 | 135x110 | 105x80 | 12 | K | 1000 | 510S-OSK200 | 510SF-OSK200 | |
| 250 | 60 | 300 | 135x110 | 105x80 | 12 | K | 1200 | 510S-OSK250 | 510SF-OSK250 | |

ELETTROSALDATO PESANTE DOPPIA RUOTA- PIASTRA FISSA

| | | | | | | M | | ART. |
|-----|----|-----|---------|---------|------|---|------|-------------|
| 125 | 45 | 176 | 175x140 | 140x105 | 13 | G | 1200 | 559G-OSG125 |
| 125 | 45 | 176 | 175x140 | 140x105 | 13 | K | 1200 | 559G-OSK125 |
| 150 | 45 | 190 | 175x140 | 140x105 | 13 | G | 1200 | 559G-OSG150 |
| 150 | 45 | 190 | 175x140 | 140x105 | 13 | K | 1200 | 559G-OSK150 |
| 175 | 45 | 217 | 175x140 | 140x105 | 13 | G | | 559G-OSG175 |
| 175 | 45 | 217 | 175x140 | 140x105 | 13 | K | | 559G-OSK175 |
| 200 | 50 | 250 | 175x140 | 140x105 | 13 | G | | 559G-OSG200 |
| 200 | 50 | 250 | 175x140 | 140x105 | 13 | K | | 559G-OSK200 |
| 250 | 60 | 300 | 250x200 | 210x160 | 17,5 | K | | 559M-OSK250 |

ELETTROSALDATO PESANTE DOPPIA RUOTA - PIASTRA GIREVOLE

| | | | | | | M | | ART. | CON FRENO ART. |
|-----|----|-----|---------|---------|------|---|------|-------------|----------------|
| 125 | 45 | 176 | 175x140 | 140x105 | 13 | G | 1200 | 560G-OSG125 | 560GF-OSG125 |
| 125 | 45 | 176 | 175x140 | 140x105 | 13 | K | 1200 | 560G-OSK125 | 560GF-OSK125 |
| 150 | 45 | 190 | 175x140 | 140x105 | 13 | G | 1200 | 560G-OSG150 | 560GF-OSG150 |
| 150 | 45 | 190 | 175x140 | 140x105 | 13 | K | 1200 | 560G-OSK150 | 560GF-OSK150 |
| 175 | 45 | 217 | 175x140 | 140x105 | 13 | G | | 560G-OSG175 | 560GF-OSG175 |
| 175 | 45 | 217 | 175x140 | 140x105 | 13 | K | | 560G-OSK175 | 560GF-OSK175 |
| 200 | 50 | 250 | 175x140 | 140x105 | 13 | G | | 560G-OSG200 | 560GF-OSG200 |
| 200 | 50 | 250 | 175x140 | 140x105 | 13 | K | | 560G-OSK200 | 560GF-OSK200 |
| 250 | 60 | 300 | 250x200 | 210x160 | 17,5 | K | | 560M-OSK250 | 560MF-OSK250 |