

## SERIE 8KVG



Ruota con nucleo centrale in ghisa meccanica con rivestimento in poliuretano  $92 \pm 2$  Shore A.

La particolare miscela consente resistere a temperature da  $-20^{\circ}\text{C}$  a  $+80^{\circ}\text{C}$ . Possiede un'ottima resistenza all'abrasione ed al contatto con olii e grassi. Garantisce a distanza di anni un'ottima scorrevolezza e una completa protezione dei pavimenti, sopportando carichi gravosi.

MOZZO: K = Cuscinetti a sfera.

SUPPORTO: Lamiera d'acciaio stampato e zincato, gruppo rotante realizzato con doppia corona di sfere.








Wheel with central core in mechanical cast iron with polyurethane  $92 \pm 2$  Shore A coating. The particular compound resists to temperatures from  $-20^{\circ}\text{C}$  to  $+80^{\circ}\text{C}$ . It has a good resistance to abrasion and contact with oils and greases. Years later, it guarantees excellent smoothness and complete protection of floors, withstanding heavy loads.

HUB : K = Ball bearing.

BRACKET: Pressed steel, zinc plated. Swivel housing with double balls race ring.

## RUOTA

				M		ART.
80	25	26	15	K	200	R8-KVG-080
100	30	30	15	K	250	R8-KVG-100
125	30	35	15	K	300	R8-KVG-125
150	40	40	20	K	500	R8-KVG-150
175	40	40	20	K	650	R8-KVG-175
200	50	60	20	K	900	R8-KVG-200

## MEDIO - PIASTRA FISSA



						M		ART.
80	25	108	100x85	80x60	9	K	200	453L-8KVG080
100	30	135	100x85	80x60	9	K	250	453L-8KVG100
125	30	162	100x88	80x60	9	K	300	453L-8KVG125
150	40	186	100x84	80x60	9	K	300	453L-8KVG150
150	40	195	134x114	105x80	12	K	500	453P-8KVG150
175	40	230	134x114	105x80	12	K	650	453P-8KVG175
200	50	242	134x114	105x80	12	K	700	453P-8KVG200

## MEDIO - PIASTRA GIREVOLE



							M			ART.	CON FRENO ART.
80	25	108	100x84	80x60	9	43	K	113	200	454L-8KVG080	454LF-8KVG080
100	30	135	100x84	80x60	9	47	K	114	250	454L-8KVG100	454LF-8KVG100
125	30	162	100x84	80x60	9	51	K	128	300	454L-8KVG125	454LF-8KVG125
150	40	186	100x84	80x60	9	46	K	128	300	454L-8KVG150	454LF-8KVG150
150	40	195	132x110	105x80	12	62	K	157	500	454P-8KVG150	454PF-8KVG150
175	40	230	132x110	105x80	12	61	K	158	650	454P-8KVG175	454PF-8KVG175
200	50	242	132x110	105x80	12	61	K	158	700	454P-8KVG200	454PF-8KVG200

## MEDIO - ATTACCO A FORO



					M			ART.	CON FRENO ART.
80	25	108	12	43	K	113	150	454LOB-8KVG080	454LFOB-8KVG080
100	30	130	12	42	K	114	150	454LOB-8KVG100	454LFOB-8KVG100
125	30	159	12	51	K	128	200	454LOB-8KVG125	454LFOB-8KVG125
150	40	193	12	62	K	158	300	454POB-8KVG150	454PFOB-8KVG150
175	40	228	12	61	K	158	350	454POB-8KVG175	454PFOB-8KVG175
200	50	240	12	61	K	158	350	454POB-8KVG200	454PFOB-8KVG200