



SERIE 9 ALETTATA



 Ruota con nucleo centrale in nylon 6 nero a raggi e rivestimento in poliuretano ad iniezione 95 Shore A. Questo tipo di ruota ha le stesse caratteristiche della ruota in nylon: scorrevolezza, resistenza all'abrasione, agli urti, all'usura, alle sostanze corrosive, ma con minore rumorosità e completa protezione dei pavimenti. Resistente a temperature da -20° C a +80° C.

MOZZO: K = Cuscinetti a sfera

SUPPORTO: Lamiera d'acciaio stampato e zincato, gruppo rotante realizzato con doppia corona di sfere.






 Injected thermoplastic polyurethane 95 Shore A wheel with black nylon 6 central core. This wheel has the same characteristics of nylon wheel: good flowability, resistance to abrasion, shock, usury and corroding substance, but with low noisy and complete flooring protection. It resists to temperature from -20 ° C to +80 ° C.

HUB: K = Ball bearings

SUPPORT: Pressed and

galvanized steel sheet, rotating group made with double crown of balls.

RUOTA

				M		ART.
100	40	40	15	K	300	R9-K-100-AL
125	45	49	20	K	400	R9-K-125-AL
150	50	55	20	K	500	R9-K-150-AL
160	50	55	20	K	500	R9-K-160-AL
200	55	60	20-25	K	800	R9-K-200-AL

MEDIO - PIASTRA FISSA



							M		ART.
100	40	135	100x85	80x60	9	K	300	453L-9K100-AL	
125	45	161	100x85	80x60	9	K	400	453L-9K125-AL	
125	45	164	134x114	105x80	12	K	400	453P-9K125-AL	
150	50	195	134x114	105x80	12	K	500	453P-9K150-AL	
160	50	200	134x114	105x80	12	K	500	453P-9K160-AL	
200	55	242	134x114	105x80	12	K	700	453P-9K200-AL	

MEDIO - PIASTRA GIREVOLE



								M		ART.	CON FRENO ART.
100	40	135	100x84	80x60	9	47	K	114	300	454L-9K100-AL	454LF-9K100-AL
125	45	161	100x84	80x60	9	51	K	128	400	454L-9K125-AL	454LF-9K125-AL
125	45	164	132x110	105x80	12	62	K	158	400	454P-9K125-AL	454PF-9K125-AL
150	50	195	132x110	105x80	12	62	K	158	500	454P-9K150-AL	454PF-9K150-AL
160	50	200	132x110	105x80	12	62	K	158	500	454P-9K160-AL	454PF-9K160-AL
200	55	242	132x110	105x80	12	61	K	158	700	454P-9K200-AL	454PF-9K200-AL

MEDIO - PESANTE - ATTACCO A FORO



						M		ART.	CON FRENO ART.
100	40	130	12	42	K	114	300	454LOB-9K100-AL	454LFOB-9K100-AL
125	45	159	12	51	K	128	300	454LOB-9K125-AL	454LFOB-9K125-AL
125	45	163	12	62	K	158	350	454POB-9K125-AL	454PFOB-9K125-AL
150	50	193	12	62	K	158	350	454POB-9K150-AL	454PFOB-9K150-AL
160	50	198	12	62	K	158	350	454POB-9K160-AL	454PFOB-9K160-AL
200	55	240	12	61	K	158	350	454POB-9K200-AL	454PFOB-9K200-AL